



KingStone\_ Premium is a Engineered Woven Coated product made with iLOCK and Indo Swiss Technology.

KingStone\_Engineered Woven Coated Product is ideal for use in Protection of all weather, Wrapping and Covering applications. The durable, stress crack resistant, lightweight construction of KingStone provides outstanding performance in many different climates and environmental conditions.



**KingStone\_Engineered Woven Coated Product** ideal for applications such as Tarpaulin, Truck Covers, Temporary Shade, Fumigation Covers, potable water reservoirs etc.

Property	Test Method	KingStone _ 225	KingStone_250
Product weight	ASTM D 751	225	250
Product Width (Inch)	ASTM D 751	108	108
Breaking Strength (Kgf/2")			
Machine Direction	ASTM D 751	120	130
Cross Direction	ASTM D 751	120	130
Elongation at Break (%)			
Machine Direction	ASTM D 751	20%	20%
Cross Direction	ASTM D 751	20%	20%
Tear Strength (Kgf)			
Machine Direction	ASTM D 4533	25	22
Cross Direction	ASTM D 4533	25	22
Low Temp flexibility	ASTM D 2136	-50 Deg C	-50 Deg C

- 1) Values are typical and not limiting specifications
- 2) MD & CD refers to machine and cross direction.
- 3) Warranty buried and exposed data is general recommendation





